Pentafill® A25

Automatic machine for filling and sealing single-dose plastic containers

Automatic machine for filling and

sealing single-dose plastic containers in a sterile or non-sterile environment.





Overview

The Pentafill A25 automatic machine provides 25 cycles per minute production speed in a compact footprint for filling and sealing your plastic containers in 5-vial strips.

- Automatic loading
- Compact machine; suitable for small rooms
- Easy-to-use machine with quick changeover capability and easy maintenance
- Maximum flexibility and versatility enabling you to fill different plastic containers and capacities
- Suitable for pharmaceutical products, diagnostics, veterinary, cosmetics, nutritional supplements and other products in liquid, gel or cream form
- Different filling systems available to fill different products viscosities
- Pentafill A25 supported formats: 0.33 - 0.6 - 1 - 2 - 3 - 5 - 10 ml

For additional information, please visit: www.lfofamerica.com







Pentafill® A25

Automatic machines for filling and sealing single-dose plastic containers



Pentafill A25 Technical Data

	A25				
Capacity	Up to 25 strips/min Up to 125 vials/min				
Voltage	220V/380V - 50/60 Hz				
Power	5 -8 Kw				
Compressed air consumption (SCFM)	21				
Required pressure	> 6 bar				
Chiller: water consumption	0.5 to 0.8 gal/min				
Chiller: MIN pressure	2 bar				
Chiller: water temperature	14/16 °C				
Weight (lbs)	2458				
Dimensions (inches)	157″ x 39″ x 71″				

Pentafill model	Feeding system	Number of strips* per minute**	Number of vials per minute**	Number of nozzles	Strips per month** per 8-hour shift***	Vials per month** per 8-hour shift***	Estimated lead time
L	Manual	2	10	1	_	-	1 month
M5	Manual	5	25	1	45,000	225,000	3 months
A5	Automatic	5	25	1	45,000	225,000	3 months
M10	Manual	10	50	2	90,000	450,000	4 months
A10	Automatic	10	50	2	90,000	450,000	4 months
A15	Automatic	15	75	3	135,000	675,000	5 months
A25	Automatic	25	125	5	225,000	1,125,000	5 months
A50	Automatic	50	250	10	450,000	2,250,000	6 months

*5-count strips

**up to

***At 85% efficiency

Please contact us to discuss how we can discuss your filling and sealing equipment needs: Inquire@tekni-plex.com.

Pentafill® is a registered trademark of Lameplast S.P.A, a Tekni-Plex business

DISCLAIMER: Actual machine dimensions may vary based on optional equipment. This machine is protected by domestic and foreign patents. The information set forth herein is subject to change without notice and should not be used as a substitute for your own independent investigation and business judgment. No intellectual property rights are conveyed hereby. TEKNI-PLEX DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE.

